Practical machine learning and its potential application to problems in agriculture

Ian H. Witten, Sally Jo Cunningham,
Geoffrey Holmes, Robert J. McQueen, Lloyd A. Smith
Department of Computer Science
University of Waikato
Hamilton, New Zealand
ihw@waikato.ac.NZ

ABSTRACT
One of the most exciting and potentially far-reaching developments in contemporary computer science is the invention and application of methods of machine learning. These have evolved from simple adaptive parameter-estimation techniques to ways of (a) inducing classification rules from examples, (b) using prior knowledge to guide the interpretation of new examples, (c) using this interpretation to sharpen and refine the domain knowledge, and (d) storing and indexing example cases in ways that highlight their similarities and differences. Such techniques have been applied in domains ranging from the diagnosis of plant disease to the interpretation of medical test data. This paper reviews selected methods of machine learning with an emphasis on practical applications, and suggests how they might be used to address some important problems in the primary production industries, particularly agriculture.

---

1. Introduction

The knowledge sector of modern economies has grown extremely rapidly, and the value of knowledge is now reckoned to be a major economic force. Contemporary thinking views an enterprise's knowledge in its domain of expertise as perhaps its most valuable asset. Much of this asset, however, is either hidden in databases as information that has not yet been teased out and made explicit, or locked up in individual principals and employees. Machine learning is a technique that can discover previously unknown regularities and trends in databases and also helps people to explicate and codify their knowledge and expertise. It therefore has great potential to contribute to the economy in many different ways.

This paper reviews selected methods of machine learning in a practical, problem-oriented context, and then goes on to examine its potential application in New Zealand primary production industries—particularly those related to agriculture. Following a brief discussion of what is meant by "learning," the next section reviews the state of the art in practical machine learning. We focus on the two machine learning paradigms that seem most promising for immediate application: similarity-based learning and case-based learning. Examples described in some detail include a plant disease identification problem and a diagnosis problem in the area of clinical audiology. Section 3 surveys expert systems in agriculture, which provide a promising application area of national importance for machine learning techniques. The final section discusses the criteria that characterize likely applications, and considers four areas in more detail: the wine industry, a particular weed control problem, dairy herd improvement, and dairy product manufacturing.

"Learning" is a very broad term which denotes the gaining of knowledge, skill and understanding from instruction, experience or reflection. We will take it in a much more specific sense to denote *the acquisition of structural descriptions from examples of what* *is being described*. Others have defined terms such as "generalization" [Schank *et al*., 1986], "inductive learning" [Michalski, 1983], and "inductive modeling" [Angluin & Smith, 1983] in almost identical ways. Not only are these all used to mean much the same thing, but what is learned is sometimes called a "generalization," a "description," a "concept," a "model," an "hypothesis." We will not attempt to make distinctions between terms such as these, but will use the term "concept" to denote the structural description that the machine acquires.

Our sense of "learning" implies the acquisition of descriptions that make the structure of generalizations explicit. This rules out a number of interesting paradigms of machine learning that parallel the skill acquisition process in people by learning *how* to do something but without making explicit the structural descriptions involved. Examples are connectionist models of learning, which embed knowledge in high-dimensional numerically-parametrized spaces and thereby make learning into a process of weight adjustment; genetic algorithms, which emulate an evolutionary form of "learning" by mutation and natural selection; and adaptive text compression, which creates a model of incoming text and uses it to predict upcoming characters. These fall outside the scope of the present paper.

2. Methods of machine learning

There are four main approaches to machine learning of structural descriptions. In *similarity-based learning*, the space of concept descriptions is delineated in advance and searched for concepts which best characterize the structural similarities and/or difference between known examples. There is a fundamental distinction between exact approaches, which guarantee to produce just that set of concepts which are consistent with the examples, and heuristic methods, which come up with a "good" concept but not necessarily the best one. In *explanation-based learning*, prior knowledge in the form of a "domain theory" is used to guide the interpretation of new examples. What is learned is not so much new knowledge, for the domain theory already contains a complete and consistent prescription for interpreting all the examples that will be encountered, but rather new and more efficient ways of employing that theory to interpret examples. Clearly the assumption of a fully comprehensive domain theory is unrealistic in virtually all practical applications of machine learning, and *combined explanation- and similarity-based learning* is an attempt to weaken it by assuming an incomplete domain theory and augmenting it by processing new examples and incorporating them into the theory, either to correct erroneous parts or to add new rules to the theory. Finally, in *case-based learning*, example cases are stored and indexed in ways that highlight similarities and differences between them, and retrieved to aid in the interpretation of new, unseen, cases.

Machine learning is a young field of research, and the methods that are best understood tend to be ones that suffer from serious drawbacks. Either they are computationally infeasible in all but very simple situations (such as exact similarity-based learning), they are not too far removed from conventional statistical methods (such as approximate similarity-based learning), or they make assumptions so rigorous as to be untenable in practical situations (such as explanation-based learning). Nevertheless, the last two or three years have seen a substantial increase in our understanding of the application of ultimately more promising methods such as combined explanation- and similarity-based learning, and case-based learning. The sections below examine first the nature of the problem domain and how this affects learning, and then look in detail at examples of similarity-based and case-based learning that seem potentially relevant to applications in agriculture. Space does not permit a treatment of the role of explanation-based learning as well.

2.1 Characterizing the problem

The most important feature of a problem domain, as far as the application of machine learning is concerned, is the form that the data takes. Most learning techniques that have actually been applied in practice assume that the data is presented in a simple attribute-value format in which a record has a fixed number of constant-valued fields or properties. Figure 1a illustrates different kinds of data type: nominal attributes, which are drawn from a set with no further structure; linear attributes, which are totally ordered; and tree-structured attributes, which form a hierarchy or partial order. Figures 1b and 1c show a sample object (or "entity"), and a sample concept (that in fact subsumes the object), expressed as a vector of generalized attributes.

Attribute vectors cannot describe situations that involve relations between objects. In actuality, of course, databases are generally expressed as a set of relations, with several records for a single entity and fields that reference other records or relations. Relations can be described by functions which, like attributes, may be nominal, linear, or tree-structured. For example, the result of a function *relative-position* that takes two-dimensional objects as arguments could be a pair of linear values *x-distance*, *y-distance*. Alternatively it could be tree-structured, as illustrated in Figure 2a. Objects and concepts in such domains are characterized by combinations of predicates (Figures 2b and 2c). Researchers in machine learning are shifting their attention from algorithms that operate in attribute-value domains to ones designed for more structured relational domains.

Another important feature of a problem domain is the quality of the data that is available. Most "real" data is imperfect: incomplete (missing values for some attributes and objects), irrelevant (some fields that do not relate to the problem at hand), redundant (involving unknown, or at least unexpressed, relations between the attributes), noisy (some attributes have inherent measurement errors) and occasionally erroneous (e.g. incorrectly transcribed). Methods of machine learning need to be robust enough to cope with



Figure 1 Attribute domain (adapted from [Haussler, 1987])

imperfect data and to discover laws in it that may not always hold but are useful for the problem at hand. The seven levels of quality shown in Table 1 can be distinguished in a data set [Gaines 1991]. The aim of a learning system is to discover a complete, correct, and minimal set of decision rules (level 1), given information at one of the other levels.

Another feature that strongly influences machine learning is whether or not operation needs to be incremental. In many situations, new examples appear continually and it is essential that the system can modify what it has already learned in the light of new information. Learning is often exceedingly search-intensive and it is generally infeasible to reprocess all examples whenever a new one is encountered.

2.2 Similarity-based learning: using search to find all possible solutions

The idea of similarity-based learning is nicely illustrated with an oft-quoted early success: the identification of rules for diagnosis of soybean diseases. Although this may sound an obscure domain, in fact the soybean crop is of great importance in a large part of the world. The similarity-based learning program AQ11 was used to analyze data from 630 questionnaires describing diseased plants [Michalski & Chilausky, 1980]. Each plant was measured on 49 attributes, and Figure 3a shows a sample record with values of some of the attributes given in italics. Each attribute has a small set of possible values (less than 7 in each case), and the record is coded as a 49-element vector of integers. The 50th attribute is the diagnosis of an expert in plant biology. There are 17 disease categories altogether.

An example rule produced by AQ11 is shown in Figure 3b. It is expressed as a disjunction (OR) of conjunctive (AND-ed) selectors, each selector comparing a particular attribute with a constant value (or range of values). The language in which concepts are



Figure 2 Structure domain (adapted from [Haussler, 1987])

expressed is a crucial factor in determining both the complexity of the learning procedure and the kind of concepts that can be learned. The rule of Figure 3b illustrates the potential role of domain knowledge in machine learning, for in fact the disjunction it contains is trivial! The only difference between the two descriptions is leaves=*normal* versus leaf-malformation=*absent*, and one of these happens to be a special case of the other, rendering the disjunction unnecessary if only the system had been aware of that fact.

The diagnostic rule of Figure 3b for Rhizoctonia root rot was generated by AQ11, along with a rule for every other disease category, from 290 training instances which were carefully selected from the corpus of 630 cases as being quite different from each other—"far apart" in the instance space. At the same time, the plant pathologist who had produced the diagnoses was interviewed and his expertise was translated into diagnostic rules using the standard knowledge-engineering approach. Surprisingly, the computer-generated rules outperformed the expert-derived rules on the remaining 340 test instances—they gave the correct disease top ranking 97.6% of the time, compared to only 71.8% for the expert-derived rules [Michalski & Chilausky, 1980]. Furthermore, according to Quinlan (in [Piatetsky–Shapiro & Frawley, 1991]), not only did AQ11 find rules that outperformed those of the expert collaborator, but the same expert was so impressed that he adopted the discovered rules in place of his own!

AQ11 converts the problem of learning discrimination rules into a series of simpler learning problems, one for each disease category. It considers all training instances of a particular category to be positive examples and all other training instances to be negative ones. The AQ11 program is nearly equivalent to repeated application of the "candidate elimination" approach to concept learning [Cohen & Feigenbaum, 1982], and to convey the general idea of how it works we will briefly sketch that method.

The candidate elimination algorithm presupposes a language in which objects are expressed (e.g. a 49-element vector of integers in the soybean case), a language in which descriptions are expressed (e.g. a disjunction of conjunctive selectors), a predicate which determines whether a particular object matches a particular description, and a partial ordering on descriptions, interpreted as generalization/specialization [Mitchell, 1982]. Given a set of positive and negative examples of a target description, the problem is to find all descriptions that are consistent with the examples. This set of descriptions is called the "version space."

In principle, the problem can be solved by enumerating descriptions and striking out those which do not fit the examples that are presented. A positive example rules out all

1	Minimal rules	A complete, correct, and minimal set of decision rules
2	Adequate rules	A complete and correct set of rules that nevertheless contains redundant rules and references to irrelevant attributes
3	Critical cases	A critical set of cases described in terms of a minimal set of relevant attributes with correct decisions
4	Source of cases	A source of cases that contains such critical examples described in terms of a minimal set of relevant attributes with correct decisions
5	Irrelevant attributes	As for 4 but with cases described in terms of attributes which include ones that are irrelevant to the decision
6	Incorrect decisions	As for 4 but with only a greater-than-chance probability of correct decisions
7	Irrelevant attributes and incorrect decisions	As for 5 but with only a greater-than-chance probability of correct decisions

Table 1 Levels of quality of input [Gaines, 1991]

descriptions that it does not match, while a negative one eliminates those it does match. As each example is encountered, the set of remaining descriptions shrinks (or stays the same). If only one is left, it is the target description. If several are left, they may still be used to classify unknown objects. An unknown object which matches all remaining descriptions is included in the target; if it fails to match every one it is excluded by the target description. Only when it matches some descriptions but not others is there ambiguity; in this case if the classification of the object were known it would cause the version space to shrink.

The method can be made more efficient by taking advantage of the partial ordering on descriptions. In fact, the descriptions in the version space need not be stored explicitly but can be inferred from the version space's upper and lower boundaries in the partial order. The upper boundary comprises all members that are maximally general, the lower boundary all that are maximally specific. The boundaries can be updated incrementally as new examples are encountered. The upper boundary is initialized to comprise all maximally general descriptions (there may be several). In principle, the lower one could be initialized to comprise all maximally specific descriptions; since there may be a large number of these it is instead initialized to include the first example only (which must be positive). This is called the "candidate elimination" or "version space" algorithm.

2.3 Similarity-based learning: heuristic approach

The version space method, in effect, locates precisely that set of concept descriptions that is consistent with all examples seen so far. It suffers from two serious drawbacks: computational complexity and sensitivity to noise. For most real-world problems it is infeasibly slow, and the soybean example of ~300 carefully-chosen training cases with ~50 attributes each is probably close to a practical upper bound on problem size.

Environmental descriptors		Condition of leaves	Condition of stem
time of occurrence	*July*	leaf spots	stem lodging
precipitation	*above normal*	leaf spot colour	stem cankers
temperature	*normal*	colour of spot on other side	canker lesion colour
cropping history	*4 years*	yellow leaf spot halos	reddish canker margin
damaged area	*whole fields*	leaf spot margins	fruiting bodies on stem
severity	*mild*	raised leaf spots	external decay of stem
plant height	*normal*	leaf spot growth	mycelium on stem
		leaf spot size	external discolouration
Condition of seed	*normal*	shot-holing	location of discolouration
mould growth	*absent*	shredding	internal discolouration
discolouration	*absent*	leaf malformation	sclerotia
discolouration colour	—	premature defoliation	
size	*normal*	leaf mildew growth	Condition of roots
shriveling	*absent*	leaf discolouration	root rot
		position of affected leaves	root galls or cysts
Condition of fruit pods	*normal*	condition of lower leaves	root sclerotia
fruit pods	*normal*	leaf withering and wilting	
fruit spots	*absent*		
			Diagnosis *Brown spot*

(a)

Rhizoctonia root rot	IF	[leaves=*normal* AND stem=*abnormal* AND stem-cankers=*below-soil-line* AND canker-lesion-colour=*brown*]
	OR	[leaf-malformation=*absent* AND stem=*abnormal* AND stem-cankers=*below-soil-line* AND canker-lesion-colour=*brown*]

(b)

Figure 3 Example record and rule in the soybean disease classification problem

Moreover, if there are any errors in the training examples (for example, measurement noise, transcription error, or incorrect classifications) the method breaks down because the version space disappears—because if the examples contain inconsistency then *no* description covers them all!

An alternative approach to searching for consistent and correct concept descriptions is to use the training set to construct a decision tree or collection of rules which discriminates positive from negative examples. In the case of a tree, the root specifies an attribute to be selected and tested first; then depending on its value, subordinate nodes dictate tests on further attributes. The leaves are marked to show the classifications of the objects they represent. For two-class problems these classifications are simply "positive" and "negative", but the method can easily be extended to the multi-class case. In the case of production rules, the training set is used to construct a set of rules which can be interpreted by an expert system in standard forward- or backward-chaining manner. In both cases, it is normally assumed that all examples are available and can be processed together to construct the tree or rules.

The ID3 algorithm is a popular machine learning method that produces a decision tree from examples [Quinlan, 1986]. It has been embodied in several commercial knowledge-engineering products. It uses an information-theoretic heuristic to determine which attribute should be tested at each node, looking at all members of the training set which reach that node and selecting the attribute that most reduces the entropy of the positive/negative decision. By the nature of the algorithm, correct performance is guaranteed on the training set. Any "generalization" achieved depends purely on the representation of objects and the choice of training set. By seeking the simplest decision tree, ID3 finds the most economical way to classify the examples given.

An example of operation of ID3 (from [Cendrowska, 1987]) concerns an adult spectacle wearer who consults an optician with a view to purchasing contact lenses, bringing along their spectacle prescription. We assume that, from the optician's point of view, this is a three-category problem with our factors *a*, *b*, *c* and *d* to take into consideration. The complete decision table is given in Figure 4a and ID3 produces the tree shown in Figure 4b. Figure 4c shows the equivalent set of rules, expressed in a form suitable for use by a simple expert system shell. Although these rules provide a concise characterization of the decision tree, they could be made even simpler. Figure 4d shows a simpler set of rules which are in fact equivalent but cannot be represented in the form of a decision tree; they were induced by the PRISM program that infers rules directly from the data without going through a decision-tree stage first [Cendrowska, 1987].

A more realistic example is the use of ID3 for assessing credit card applications [Carter & Catlett, 1987]. Attributes such as bank balance, monthly expenditure, monthly disposable income, employment status, home status, time at address, age of car, and so on are used to form a decision tree to determine whether an applicant is creditworthy or not. Sample cases can be obtained from past applications and the result of the existing assessment method. Clearly, unlike the contact lens example of Figure 4, only a small subset of possible combinations of attributes will be represented in the training data, and so the decision tree is used to *generalize* from the training set rather than simply to summarize it. Also, creditworthy/noncreditworthy categorization is far more subjective than the disease classification in the soybean example, and some noise and inconsistency is only to be expected. Carter & Catlett [1987] conclude that machine learning techniques compete well with existing methods for credit assessment by specially-trained experts.

The ID3 procedure has been thoroughly studied and extended in several different directions. Machine learning by the induction of decision trees has been given a sound theoretical footing [Quinlan & Rivest, 1989]. Variants have been designed for use in